



ADDABOUND RESIN BOUND SURFACING CARE AND MAINTENANCE GUIDE

Every effort has been made to ensure your Addabound surface is of the highest quality. However, it will look better and last longer if a few simple maintenance procedures are adopted.

Routine maintenance

The Addabound surface should be regularly swept clean, removing leaves and detritus material in order to prevent moss growth. If the surface has been contaminated with chewing gum it is best removed by freezing and chipping off as necessary. Removal of individual pieces of chewing gum can be achieved by treating each piece with a freezing spray and then scraping off the gum with a suitable scraper. For more extensive gum removal contact a specialist cleaning contractor.

Vegetation

Any moss or weed growth that occurs should be treated using an appropriate herbicide. Any ingrained algal growth can be removed and the color of the original Addabound surface restored by applying a strong bleach solution. The bleach solution however should be applied in accordance with manufacturer's guidelines and in compliance with local environmental regulations. After application of the bleach solution, the surface must be rinsed well with clean water.

Normal/abnormal use

The Addabound surface has been designed for normal pedestrian and vehicular traffic use. Therefore protection should be provided wherever possible against abnormal usage.

Abnormal usage applies to heavy objects such as roll-off containers and dumpsters. These should not be dragged across the surface. The Addabound must be protected in this instance to avoid any impact damage, staining etc. Spillage of gasoline or solvents should be avoided as these will soften and damage the resin binder.

General cleaning

General cleaning of the surface can be carried out by cold pressure washing to remove dirt and grime. Care should be taken however to prevent damage to the surface with excessive water pressure (up to 1500 psi rating). Only cold water should be used and the water lance should be kept at least 8 inches from the surface. If the surface is contaminated with any cement or concrete marks these can be removed using dilute hydrochloric acid or a proprietary cement remover. In all cases we recommend that a small area is carried out first to confirm suitability.

Damage repair

Should the surface be damaged we can supply small repair kits and we would suggest that these are carried out at the earliest convenience and by a certified Chameleon Ways applicator.

The information given is intended as a guide only in the care and maintenance of the Addabound finish. Chameleon Ways cannot accept any responsibility for the improper reliance upon or misuse of the information. Product design and specification are subject to change without notice.